

# **W** Berkelmans **WELDING** *& Manufacturing Inc.*

## **4 Ton Farm Dump Trailers**

5 feet wide, x 10 feet long x 18" deep. (75 cubic feet)

3/16 plate floor and sides bent as one pan.

10 gage unibody long sill welded 100% to the floor.

3" x 5" x .188 tube main frame.

2" x 4" x .188 tube tongue.

2" x 4" back post.

Pockets inside for board extensions.

24" high tailgate.

Spreader chains on tailgate.

Self locking and unlocking tailgate, tailgate is removable.

Swivel clevis hitch with 1.1/16" pin hole.

7000 lb drop leg trailer jack.

Hitch height 15".

5000 lb per spindle and hub load rating, 6 bolt hub. Spindles are replaceable.

12.5 L 15 12 ply rating tires on 6 bolt rims.

24" x 4" hydraulic cylinder.

Trailer is 49" from ground to top of side.

10 feet height clearance at highest point when dumping.

50 degree dump angle.

Trailer total length is 165"

Trailer weighs 1400 lbs.

Chemical wash, rust inhibitor, adhesive spray, 2 part epoxy primers

- and paint to choice of Cat yellow, John Deere green, Agri. red, and Kubota orange.

Trailer lights, reflectors and slow moving vehicle sign.



**Berkelmans Welding Inc. County Road 52, RR#7, Aylmer, ON N5H 2R6**  
**phone 519-765-4230 fax 519-765-4507**  
**www.berkelmanswelding.on.ca**